Cleaning Outdrive Units



BOAT Magic is the most effective way to clean and remove marine stains and discoloration from most boat outdrive units. Different applications require different methods and dilutions.

READ INSTRUCTIONS IN THEIR ENTIRETY BEFORE PROCEEDING.

DILUTION:

• Dilute 1 part BOAT Magic to 2 parts water.

PRECAUTIONS:

- Extreme caution must be used when applying BOAT Magic full strength to aluminum surfaces.
- Use extreme caution when applying BOAT Magic full strength to outdrive components as prolonged exposure of aluminum surfaces to BOAT Magic may cause a reaction.
- While using BOAT Magic, protective eyewear and gloves are always required.
- Active ventilation is required when working indoors.
- Plastic should be used to cover the boat trailer to reduce risk of corrosion to the trailer.
- When diluting, ALWAYS add the BOAT Magic to water, NOT water to the BOAT Magic. This eliminates the potential of an unwanted reaction that may cause dangerous splashing to occur.
- DO NOT dump BOAT Magic into lakes, rivers, oceans, or other bodies of water.
- Collect wastewater and dispose according to all local, state, and federal regulations.
- Ensure proper metal and equipment integrity prior to using BOAT Magic.
- Consult the manufacturer of the outdrive unit for product compatibility prior to use.

APPLICATION:

- Protect instrumentation connected to the out drive unit prior to cleaning.
- Apply diluted solution with acid resistant sprayer or with natural bristle brush.
- Let dwell no more than 10 minutes.
- Softly scrub surface with soft natural bristle brush, if necessary, to remove especially stubborn stains.
- Rinse thoroughly.
- Repeat if necessary.



BOAT Magic is not an algaecide or molluscide and is not intended to repel or control the growth of algae or marine life.

GT INDUSTRIAL SALES

Phone: 866-525-3615 gtindustrialsales.com