



#### Product Features

- Unique blend of silicon based, non-petroleum lubricants provide the necessary viscosity and stability over a wide range of temperatures.
- Special silicon suspension fluid is formulated exclusively for use in Euclid Hitachi equipment and the Accu-Trac suspension system's Neocon™ suspension strut.
- Cost-effective alternative to brand name OEM.
- Non-corrosive properties protect equipment.
- Provides more energy absorption than regular suspension/hydraulic oils.

#### Description:

Universal Suspension Fluid is a silicon suspension fluid for silicon charged struts.

#### Intended Use:

Intended for use in the struts of Hitachi/Euclid Accu-Trac struts as a direct replacement for OEM Neocon-E™ Fluid. This fluid is used in conjunction with helium or other inert gases in its strut application.

#### Product Specifications:

pH:	6.5 - 7.5
Odor:	Non-specific.
Color:	Green-blue viscous liquid.
Shelf Life:	5 years.
Disposal:	Dispose according to all local, state, and federal regulations.

#### Advantages:

Universal Suspension Fluid offers several advantages including:

- 100% compatible with Hitachi Accu-Trac Suspension.
- Economical.
- Non-corrosive properties protect equipment.
- Acceptable for use in a wide range of temperatures.
- Neutral pH.

#### Applications:

Use in accordance with OEM specifications.

#### Precautions:

Protective eyewear and clothing is recommended.

For specific technical and safety information, including SDS, please visit the GT Industrial website:  
<https://gtindustrialsales.com>



Suspension Fluid Description	Order #
5 Gallon Drum	51425/5G
55 Gallon Drum	51425/55G